

Charger Series Assault Troop Lifejackets



International Safety Products Ltd

Orrell Mount, 159 Hawthorne Road, Bootle, L20 6JU, UK

Tel +44 (0) 151 922 2202 Fax +44 (0) 151 922 5874

Email sales@ispl.co.uk Web www.ispl.co.uk

ISP is an MTR Holdings Company



Chaffenger Series Assault Troop Lifejackets

Purpose

Designed for use in Amphibious Operations and capable of supporting Combat Personnel plus up to 40kgs of equipment.

Easily discarded whilst on the move by removal of release pin.

The low profile design is compatible with most webbing patterns and is able to integrate with Paratrooper Harnesses.

For use in all Geographic Areas of extreme and adverse climates. Designed to perform after storage, at temperatures between -30°C and +70°C. When on deck, designed to perform in temperatures between -30° C and +40° C, and when worn in sea water at -1°C or above.

Description

The lifejacket comprises of an all welded, high tenacity coated polyamide inflatable stole. The stole is fixed within a covert green retaining pouch complete with stowable, high visibility patches which may be deployed or stowed as operational conditions dictate.

Comfort handles, buddy line and whistle are fitted as standard.

The stole is inflated via a manually operated system and gas cylinder. Also an oral tube is available for oral inflation or top-up/back-up.

Attached to the inside of the lifejacket cover is a deployable Sprayhood to prevent wave assault to the wearers face and airways.

All contained within a high abrasion resistant, heavy duty, outer zipped valise worn about the neck and secured around the body by 50mm webbing, adjustable harness. The harness is fixed with a quick release pin for swift removal.

The outer valise (or cover) has a 'cylinder inspection zip' to aid maintenance and pre-wear checks.

Technical Data

	Challenger 300	Challenger 400
Buoyancy	300N	400N
Gas	Carbon Dioxide	Nitrogen
Charge	60gms	62gms
Weight	1.4kgs	1.7kgs

Design Options

Manually switched Location Light Colours: Olive green, Black, DPM











